



Industrial Corded Handheld Laser Bar Code Reader

The PowerScan 8000 product series is Datalogic Scanning's premium line of rugged industrial handheld data collection products. The PowerScan PD8300 laser scanner offers state-of-the-art performance in a corded industrial product.

The PD8300 reader features Datalogic's exclusive 3 Green Lights (3GL™) for superior good read feedback. The patented 'Green Spot' directly on the code, and dual Good Read LEDs on the top and back of the cap add increased visibility at any angle. Superior reading performance is enhanced by Datalogic's patented PuzzleSolver™ technology for fast and accurate reading of standard, poorly printed and damaged codes.

The PD8300 reader's mechanics have been developed and tested to withstand extreme environmental conditions maintaining consistent reading performance without degrading performance or reliability. Its ergonomic enclosure is lightweight and well-balanced to ensure optimal operator comfort during scan intensive operations. A built-in metal tether hook for

suspended applications ensures workplace productivity.

All models have multi-interface capabilities built-in featuring the most popular interfaces; RS-232, Keyboard Wedge, Wand Emulation and USB. The Datalogic Aladdin™ configuration program provides user-friendly features that simplify the start-up procedure, even for inexperienced users.



Features

- Optics available in Standard Range (contact up to over 1.0 m / 3.3 ft) and Auto Range (10 cm / 4.0 in to over 10 m / 33.0 ft)
- Datalogic 3GL™ and loud beeper for good read feedback
- Built-in multiple interface (RS-232, Keyboard Wedge, Wand and USB)
- Undecoded Laser Output Model
- Operates over a wide range of temperatures
- Water and Particulate Sealing Rating: IP65
- Drop resistance to 2.0 m / 6.5 ft



Specifications

DECODING CAPABILITY

1D / LINEAR CODES Autodiscriminates all standard 1D codes including GS1 Databar™ linear codes
 STACKED CODES Code 16K; Code 49

ELECTRICAL

CURRENT Operating (Typical): D8330: 420 mA @ 4 V; 310 mA @ 5 V; 62 mA @ 30 V
 D8340: 500 mA @ 4 V; 370 mA @ 5V; 70 mA @ 30 V
 Standby/Idle (Typical): 4 mA
 4 - 30 VDC

INPUT VOLTAGE

ENVIRONMENTAL

AMBIENT LIGHT Immune to light exposure in offices/facilities and direct exposure to sunlight
 Withstands 50 drops from 2 m / 6.6 ft to concrete
 DROP RESISTANCE 20 kV
 ESD PROTECTION (AIR DISCHARGE) 90%
 HUMIDITY (NON-CONDENSING) IP65
 PARTICULATE AND WATER SEALING
 TEMPERATURE Operating: -30 to 50 °C / -22 to 122 °F
 Storage/Transport: -30 to 50 °C / -22 to 122 °F

INTERFACES

Keyboard Wedge; RS-232; Undecoded Laser Output-Model D8340 Only; USB; Wand

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE Yellow/Black
 DIMENSIONS 20.7 x 11.4 x 6.9 cm / 8.1 x 4.5 x 2.7 in
 WEIGHT 295.0 g / 10.4 oz

READING PERFORMANCE

LIGHT SOURCE 630 - 680 nm VLD
 Aiming: 630 - 680 nm VLD, Activated by 'Double-Click' Trigger
 PRINT CONTRAST RATIO (MINIMUM) 15%
 READ RATE (MAXIMUM) 35 +/- 5 scans/sec.
 READING ANGLE Pitch: 5 to 55° / -5 to -55°; Roll (Tilt): +/- 20°; Skew (Yaw): +/- 60°
 READING INDICATORS Beeper; Datalogic Three Green Lights (3GL™) Good Read Feedback; Datalogic 'Green Spot' on the Code, Dual Good Read LEDs
 RESOLUTION (MAXIMUM) D83X0: 0.076 mm / 3 mils; D83X0 Auto Range: 0.190 mm / 7.5 mils

READING RANGES

TYPICAL DEPTH OF FIELD Minimum distance determined by symbol length and scan angle.
 Printing resolution, contrast, and ambient light dependent.
 PD8300 5 mils: 2.1 to 13.3 cm / 0.8 to 5.2 in
 7.5 mils: 3.5 to 24.2 cm / 1.4 to 9.5 in
 10 mils: 2.9 to 42.8 cm / 1.1 to 16.8 in
 13 mils: 2.3 to 55.1 cm / 0.9 to 21.7 in
 20 mils: 6.3 to 78.5 cm / 2.5 to 30.9 in
 40 mils: 2.5 to 97.8 cm / 1.0 to 38.5 in
 PD8300 AR 7.5 mils: 7.0 to 46.5 cm / 2.7 to 18.3 in
 10 mils: 10.8 to 99.9 cm / 4.2 to 39.3 in
 13 mils: 12.7 to 147.3 cm / 5.0 to 58.0 in
 20 mils: 7.0 to 215.9 cm / 2.7 to 85.0 in
 40 mils: 16.0 to 340.0 cm / 6.3 to 133.8 in
 55 mils: 0.2 to 4.1 m / 0.7 to 13.5 ft
 Reflective -100 mils: 0.5 to 15.0 m / 1.6 to 49.2 ft

SAFETY & REGULATORY

AGENCY APPROVALS The product meets necessary safety and regulatory approvals for its intended use.
 The Quick Reference Guide for this product can be referred to for a complete list of certifications.
 ENVIRONMENTAL COMPLIANCE Complies to EU RoHS
 LASER CLASSIFICATION Caution Laser Radiation - Do not stare into beam
 CDRH Class II
 IEC 60825-1 Class 2

UTILITIES

DATALOGIC ALADDIN™ Datalogic Aladdin configuration program is available for download at no charge

WARRANTY

3-Year Factory Warranty



Cases/Holsters

- 11-0138 Heated Holder, 36 VDC
- 11-0139 Heated Holder, 24 VDC
- 11-0140 Heated Holder, 48 VDC
- HLS-P080 Universal Holster (HLS-8000)
- PC-P080 Protective Case/Belt Holster (PC-8000)



Mounts/Stand

- 7-0404 Industrial Take-Up Reel
- HLD-P080 Desk/Wall Holder (HLD-8000)
- STD-P080 Hands Free Stand (STD-8000)

© 2007-2008 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws.
 • Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo, 3GL, Datalogic Aladdin and PuzzleSolver are trademarks of Datalogic S.p.A. • PowerScan is a trademark of Datalogic Scanning Inc.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-POWERSCANPD8300-ENA4 20080725

www.scanning.datalogic.com